

# SEALANTS, GASKETS AND ADHESIVES

---

## Model ART

### Roller Type Adhesive

- Designed for bonding duct liner, duct wrap and fibrous glass insulations to painted steel, galvanized or aluminum duct
- Can also be used a contact bond adhesive in areas where water entrapment may be a problem
- This water-based product is UL listed and meets NFPA 90A and 90B 25/50 requirements
- Available in 5 gallon buckets

[Submittal Drawing - pg. 1](#)

[Submittal Drawing - pg. 2](#)

---

## Model AST

### Spray Type Adhesive



- Designed for bonding fiberglass and mineral wool duct liner to galvanized duct
- Ideal for applying with high volume spray and coil line operations
- Can also be applied by extrusion or manual spray equipment
- This water-based product is UL listed and meets NFPA 90A and 90B 25/50 requirements
- Available in 55 gallon drums

[Submittal Drawing - pg. 1](#)

[Submittal Drawing - pg. 2](#)

---

## Model SSB

### Solvent-Based Adhesive



- Designed as a high velocity duct joint sealant for indoor applications
- Can also be used to adhere duct fabrics and flexible duct to high velocity ducts
- This solvent-based product is UL listed and meets NFPA 90A and 90B 25/50 requirements
- Available in 1 gallon buckets or 11 ounce tubes

[Submittal Drawing - pg. 1](#)

[Submittal Drawing - pg. 2](#)

---

## Model SWB-N

### Water-Based Sealant



- Designed as a vapor barrier duct sealant for indoor or outdoor applications
- Can be applied to galvanized, aluminum or mild steel ducts
- It is ideal for sealing ASJ, FRK and FSK jackets and board facings at joints or laps
- Also use over staple and weld pin punctures
- The cartridge grade is an ideal joint sealant with polystyrene insulation
- This water-based product is UL listed and meets NFPA 90A and 90B 25/50 requirements
- Available in 5 or 1 gallon buckets or 11 ounce tubes

[Submittal Drawing - pg. 1](#)

[Submittal Drawing - pg. 2](#)

---

## Model SWB-R

### Water-Based Reinforced Sealant



- Designed as a vapor barrier duct sealant for indoor or outdoor applications
- Can be applied to galvanized, aluminum or mild steel ducts
- Also use over staple and weld pin punctures
- Fiber reinforcement ensures that it is tough yet flexible
- This water-based product is UL listed and meets NFPA 90A and 90B 25/50 requirements
- Available in 5 or 1 gallon buckets or 11 ounce tubes

[Submittal Drawing - pg. 1](#)

[Submittal Drawing - pg. 2](#)

---

## Model SPB

### Pumpable Butyl Sealant

- Provides a non-drying, permanently flexible seal for rigid or expansion joints on a variety of materials
- It provides a moisture and vapor tight seal
- Available in 55 gallon drums or 5 gallon buckets

[Submittal Drawing](#)

---

## Model GSK-BT Butyl Tape Gasket



[Submittal Drawing](#)

- Provides a non-drying, permanently flexible gasket
- It will adhere to a variety of clean, dry surfaces
- Contains high percentage of virgin butyl rubber to enhance its sealing and aging characteristics
- It is formulated to retain handling properties through a wide temperature range
- It will not crack or separate while being applied at low temperature ranges
- Product is 1/8" thick and 5/8" wide, and is available in 30' rolls
- Product is UL listed

---

## Model GSK-BP Butyl Patch Gasket

- Provides a non-drying, permanently flexible gasket
- It will adhere to a variety of clean, dry surfaces
- Contains high percentage of virgin butyl rubber to enhance its sealing and aging characteristics
- It is formulated to retain handling properties through a wide temperature range
- It will not crack or separate while being applied at low temperature ranges
- Product is 1/8" thick, and is available in 1"x2" and 2"x3" patch sizes
- Product is UL listed

[Submittal Drawing](#)

---

## Model GSK-NT Neoprene Tape Gasket



[Submittal Drawing](#)

- Closed cell foam comprised of neoprene, PVC and nitrile
- It has good chemical resistance and is flame rated
- Product is 5/16" thick and 3/4" wide, and is available in 50' rolls
- Product is UL listed

