


## DECK-MATE

[Deck-Mates](#) for watertight flashing of metal roof & wall systems. Deck-Mates are designed in a multitude of sizes to accommodate penetrations from 1/8" to 26" round and work in conjunction with any configuration of metal roofing or siding panel. The Portals Plus Deck-Mate is engineered with an aluminum flanged base that can be bent by hand to conform to the roof profile, irregularities, or slopes. The aluminum flange is bonded to the flexible boot during the molding process and is completely isolated from the underside of the boot to prevent any potential galvanic corrosion such as happens with solid metal flashings. Deck-Mates are available in two flexible boot materials- EPDM, with a serviceable temperature range of -60F to +270F, and Silicone, for both extremely low and extremely high temperature applications, with a serviceable temperature range of -100F to +500F. Installation is quick, easy, and secure, requiring only an approved sealant on the underside and stainless fasteners. Portals Plus [Adapter Rings](#) can further extend the capabilities of the Deck-Mates by sealing unusual shapes such as angle irons and square tubes.

	<b>SILICONE DECK-MATE - HIGH TEMPERATURE w/CLAMP</b>			
	NEW UPC PART NUMBER	DESCRIPTION	QTY/ CTN	LIST PRICE PER UNIT
	<a href="#">82016</a>	SDM#1 1/4" - 2"	15	
	<a href="#">82026</a>	SDM#2 1" - 3-1/4"	15	
	<a href="#">82036</a>	SDM#3 1/4" - 4"	15	
	<a href="#">82040</a>	SDM#4 3" - 6"	10	
	<a href="#">82050</a>	SDM#5 4" - 7"	10	
	<a href="#">82060</a>	SDM#6 5" - 9"	10	
	<a href="#">82070</a>	SDM#7 6" - 11"	10	
	<a href="#">82085</a>	SDM#8 7" - 13"	5	
	<a href="#">82091</a>	SDM#0 10" - 18"	1	
	<a href="#">82101</a>	SDM#0 13" - 26"	1	

Call Customer Service For Price