

WARD GASKET

GSK BP

Butyl Patch Gasket

About Ward Butyl Patch Gasket

Ward Butyl Patch Gasket is a permanently soft caulking compound which contains a high percentage of virgin butyl rubber to enhance its sealing properties and aging characteristics. It is formulated to retain low temperature handling properties at elevated temperatures. It will adhere to most clean, dry surfaces such as steel, galvanized steel, aluminum, plastic materials, wood, and concrete.

Ward Butyl Patch Gasket is used to provide a moisture and vapor tight seal to exclude water and dust from any given area under atmospheric pressure. It is an excellent multi-purpose gasket material for the HVAC industry, as well as many other trades and industries.

Specifications

UL Classified: As listed in file MH19835

Flame Spread 5

Smoke Developed 5

Chemical Resistance: Excellent resistance to water, alcohols, mild acids and bases

Paintability: Yes

Non-corrosive: Will not corrode metals

Physical Properties

Color: Gray, Black, or Off-White

Dimensions (T x W x L): .125 in x 1 in x 2 in (.3 cm x 2.5 cm x 5.1 cm)

.125 in x 2 in x 3 in (.3 cm x 5.1 cm x 7.6 cm)

Cone Penetration (ASTM D217-52T): Modified to total moving load of 300 gm, 5 sec at 77°F, 80-90 mm / 10

Web Elongation: 600% to 700%

Adhesive Tensile Strength: 10 to 12 psi

Temperature Tolerance Range: -40°F to 249°F (-40°C to 121°C), will not slump at 280°F (138°C)

Temperature Usage Range (Recommended): 0°F to 100°F (-18°C to 38°C)

Flexibility: No cracking at -20°F (-29°C)

Vehicle Bleedout: None

Shelf Life: One year minimum

The information contained herein we believe is correct to the best of our knowledge and tests. This information is furnished as a guide for selecting materials. Ward Industries disclaims liability for results or use of this information. It is the customer's responsibility to obtain and test samples when determining suitability of material for a particular application.

JOB NAME: _____	SUBMITTED BY: _____
LOCATION: _____	
ARCHITECT: _____	
ENGINEER: _____	
CONTRACTOR: _____	



500 E. Eighth Street • Holland, MI 49423
T (800) 466-9374 • F (866) 466-9335 • www.wardind.com